



PRODUCT NEWS

RXF 36 in a dedicated 27.5 wheel size for the highest performance 27.5 bikes. A trail for that lives for big mountain riding, there are no boundaries any more.

Implementing TTX technology in the front fork, featuring a twin tube design, enabling parallel and separated oil flow to ensure optimal pressure at all times. Controlling the pressure levels ensures initial smoothness and staying high in travel with maintained bump absorption, traction and stability.

Low and high speed compression are externally adjustable and fully independent. Thanks to the easy to tune, 3 Chamber Air spring and contrary to most of the forks available, the shape of the spring force can be adjusted, such as increasing sensitivity without bottoming out all using your regular shock pump.

Why boost? With the wider hub flange, and the stronger spoke-bracing angle, the stiffness and stability of the wheel is massively enhanced, at a tiny weight penalty, resulting in more effective and more precise bike handling.



FEATURES

- > TTX-technology
- > 27.5" fork
- > 22mm piston
- > 46mm Offset
- > Boost 15x110mm
- > 3 Chamber Air Spring
- > 15 click rebound, low speed comp, 5 click high speed comp with pedal mode
- > 650b is 2085g @ 170mm travel
- >~ Axle to crown is 563 mm @ 170 mm, 553mm @160, 543mm @150, 533mm @140 ~
- > Max tyre size: 27.5x2.8 (Actual allowed outer dimensions of tyre: 725x70 mm)



OHLINS.COM II OHLINSRACING II @ OHLINSRACING II OHLINSRACING

ÖHLINS RACING AB • Instrumentvägen 8-10 S-194 51 Upplands Väsby Sweden • +46 8 590 025 00 • info@ohlins.se